



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n  
25215 SANT RAMON  
(Lleida) - Spain  
Tel.: +34 973 524 336  
Fax: +34 973 524 381

[www.segues.es](http://www.segues.es)  
[www.seguessl.com](http://www.seguessl.com)  
[www.segues.fr](http://www.segues.fr)  
[segues@seguessl.com](mailto:segues@seguessl.com)  
[export@seguessl.com](mailto:export@seguessl.com)



## SFI-PES

TWIN DISC FERTILIZER  
SPREADER , MOUNTED WITH  
WEIGHING SYSTEM



[www.seguessl.com](http://www.seguessl.com)

[www.segues.sl.com](http://www.segues.sl.com)



## SEGUES, HIGH PRECISION IN THE DISTRIBUTION OF THE FERTILIZER

After 40 years with the farmer in the manufacture of fertilizer spreaders, the SFI-PES are distributors of fertilizer of high precision, high capacity and high reliability. Equipped with electronic weighing and control system, with a capacity to spread up to 36 m, the SFI-PES are undoubtedly essential machines to achieve optimal fertilization and the best possible harvest.

### KEY STRENGTHS:

- Integrated weighing system in the machine frame that allows us to automatically adjust the opening of the dosing gate according to the speed of the tractor and the actual flow characteristics of the used mineral fertilizers.
- 1.500 l hopper that can be converted with 3.200 l
- High precision distribution up to 36 m
- Simple adjustment of the amount of distribution and working width
- Simple and reduced maintenance
- Anticorrosive paint

### standard equipment:

- Electric servomotors to regulate the position of the closures
- Manual adjustment of fertilizer drop point
- Stainless steel filter grid
- Bottom of the stainless hopper
- Stainless discs with quick disassembly
- Quick setting for palette settings
- Pallet kit for distribution 12-24m
- Slow rotation stirrers
- Discharge tube
- Management computer



Integrated weighing system in the frame



Stainless discs



stainless steel screen



Palette 12-24 m



Regulation of the point of fall of the fertilizer

## TECHNICAL CHARACTERISTICS

Model	Upload	Hopper	Width	Length	Height	Weight	Power
<b>SFI-PES 1500</b>	3.800 kg	1.500 l	2.350 mm	1.650 mm	1.230 mm	510 kg	90-100 cv
<b>SFI-PES 2150</b>	3.800 kg	2.150 l	2.350 mm	1.650 mm	1.460 mm	545 kg	140 cv
<b>SFI-PES 2400</b>	3.800 kg	2.400 l	2.800 mm	1.650 mm	1.550 mm	570 kg	140 cv
<b>SFI-PES 2800</b>	3.800 kg	2.800 l	2.350 mm	1.650 mm	1.660 mm	580 kg	160 cv
<b>SFI-PES 3200</b>	3.800 kg	3.200 l	2.800 mm	1.650 mm	1.700 mm	585 kg	180 cv




## OPTIONAL EQUIPMENT



Ladder



Storing support with wheels



Side Deflector



Rear light kit



Disc & pallets 33-36 m