



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n  
25215 SANT RAMON  
(Lleida)  
Tel.: +34 973 524 336  
Fax: +34 973 524 381

[www.seguessl.com](http://www.seguessl.com)  
[segues@seguessl.com](mailto:segues@seguessl.com)  
[recanvis@seguessl.com](mailto:recanvis@seguessl.com)  
[export@seguessl.com](mailto:export@seguessl.com)  
[administracio@seguessl.com](mailto:administracio@seguessl.com)

[www.seguessl.com](http://www.seguessl.com)

RA

TWIN DISC AND PULL TYPE  
FERTILIZER SPREADERS



[WWW.SEGUESSL.COM](http://WWW.SEGUESSL.COM)

Twin spinner, conveyor and pull type spreaders from 6 to 10 Tn

## RA SERIES FERTILIZER DISTRIBUTORS



### SEGUÉS RA, 30 YEARS IN THE MARKET AND ON FIELD

"The SEGUÉS RA fertilizer spreaders are the proof of the Segué spreaders success, in the market for longer than 30 years, with 3 main versions of 6, 8 & 10 Tn and with many different adaptations that make this machine one of the most versatile and profitable spreader, and with an unbeatable fertilizer distribution."

#### SEGUÉS RA SPREADERS STRONG POINTS:

- Distribution by twin spinner made of stainless steel
- Perfect VRA system in all versions, mechanical and electronic.
- Very width conveyor to avoid vaults
- Spinners hydraulically driven by both hydraulic motors
- Adjustable fertilizer exit hatch to distribute any amount
- Big diameter spinners suitable to spread mineral as organic fertilizers
- Traction tyres for a lower soil compression and better pull
- The spreader can be electronically driven
- Great materials strength
- Different capacities to reach all requirements

#### TECHNICAL FEATURES

| Model | Upload    | Hopper  | Width    | Length   | Height   | Wheel      | Weight   |
|-------|-----------|---------|----------|----------|----------|------------|----------|
| RA-6  | 6.000 kg  | 5.000 l | 2.450 mm | 5.780 mm | 2.350 mm | 18.4/15-30 | 2.025 kg |
| RA-8  | 8.000 kg  | 6.500 l | 2.450 mm | 5.780 mm | 2.350 mm | 18.4/15-30 | 2.200 kg |
| RA-10 | 10.000 kg | 8.200 l | 2.450 mm | 6.320 mm | 2.360 mm | 18.4/15-34 | 2.340 kg |

#### STANDARD EQUIPMENT



Big diameter twin spinners hydraulically moved



Mechanical Jack



Traction tyres to avoid the soil compactation



Hydraulic motors to move the spinners



Mechanical VRA system as standard in all models



Adjustable hatch

#### SEGUÉS RA FERTILIZER SPREADERS AVAILABLE OPTIONS



Independent oil circuit driven by the PTO



Hydraulic tarpaulin



Hand Tarpaulin



Spinners revolutions adjuster and counter



Turning Hitch



Electronic VRA system



Hopper supplement



Mechanical working width adjusting system



Top screen to prevent large chunks from entering hopper



Inside hopper auger to can spread wet products