



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n  
25215 SANT RAMON  
(Lleida)  
Tel.: +34 973 52 43 36  
Fax: +34 973 52 43 81

[www.seguessl.com](http://www.seguessl.com)  
[segues@seguessl.com](mailto:segues@seguessl.com)  
[recanvis@seguessl.com](mailto:recanvis@seguessl.com)  
[export@seguessl.com](mailto:export@seguessl.com)  
[administracio@seguessl.com](mailto:administracio@seguessl.com)



# RAD 6000/8000

Free fall and twin spinner  
fertilizer spreaders



[www.seguessl.com](http://www.seguessl.com)



## SEGUÉS, More than 35 years performing the fertilization

Les abonadores SEGUÉS RAD ofereixen una qualitat de distribució inigualable, a més a més d'una construcció robusta i resistent amb una tremuja estudiada per a oferir la millor caiguda possible del producte, i doble disc centrífug per aconseguir amplades de treball fins a 24 m.

### RAD Strong Points

- Hydraulically driven floodgate
- Two wing kits for different width spreading
- Bigger spinners than usual for a better and wider spread
- Spinners driven by the tractor's PTO at 540 rpm
- Distribution system 100% made of stainless steel
- Two divisions inside the hopper to perform the best spinner feeding
- Galvanized and removable screen
- Double window to view inside the hopper
- Height adjustable draw bar with shocks absorber
- Screwed up and turning hitch

### Strong points



Screwed up and turning hitch



Double front window and Screen



Distribution system made of stainless steel



Adjustable draw bar with shock absorber

### Standard equipments in all SEGUÉS RAD spreaders

- Double Cardan
- Mechanical Jack
- Hydraulic brake and mechanical storing brake
- Double spreading wings kit
- Stairs to go in the hopper
- Galvanized screen made of Trames
- 385/65 R 22.5 Tyres
- Lights kit according to EU regulations



Stairs



Interior cardan and hydraulic brake



Twin independent floodgates



Mechanical and removable Jack

### Technical features

Model	Tare	Upload	Width	Height	Length	Tyres
RAD6000	2.250 kg	6.000 kg	2.550 mm	2.530 mm	4.633 mm	385/65R22,5
RAD8000	2.400 kg	8.000 kg	2.550 mm	2.730 mm	4.633 mm	385/65R22,5



### Available options in all RAD versions



Stainless steel hopper RAD6000



Stainless steel hopper RAD8000



Hand moved tarpaulin RAD6000 y 8000



Flotation tyres 500/50-17



Flotation tyres 500/50-17



Hydraulic Jack



Side deflector for both sides



Cardan with Clutch