



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n
25215 SANT RAMON
(Lleida)
Tel.: +34 973 52 43 36
Fax: +34 973 52 43 81

www.seguessl.com
segues@seguessl.com
recanvis@seguessl.com
export@seguessl.com
administracio@seguessl.com



AGROMAK-5F

THE FIVE JOBS IMPLEMENT



WWW.SEGUESSL.COM

www.seguessl.com

SEGUÉS, since 1978 providing quality and performance

The AGROMAK 5F by MAQUINARIA AGRÍCOLA SEGUÉS is the required implement to reach an optimal soil culture with a minimum time and resources investment. By only one round, it's capable to perform 5 jobs leaving the soil ready for sowing. Due to its construction, shares, discs and the roller, it opens the soil, mixes the soil, crushes the culture remains and stubbles, levels the terrain and with the roller compacts the surface

Benefits:

- High resistance tubular frame
- Tines with reversible shares and wings to open and mix with minimum effort
- 377 mm tine to tine distance
- Up to 800 mm tine height
- 680 mm tines line to line distance
- Third point hitch
- Fast hooking bar as standard
- Hydraulic folding system on wider than 3 m versions
- In all versions, tines protected by fusible link or "NO-STOP" springs
- Single sealed bushing in every disc with conic bearing for maximum protection

AGROMAK-5F strong points



Reversible shares with wings



Discs height adjustment system



Rear roller



Two tines lines with winged shares

AGROMAK-5F standard features

- Third point hitch
- Fast hooking bar
- Concave discs
- High quality cast iron tines
- Reversible shares with wings
- Tines and discs height adjustable
- 100x100 reinforced frame
- High resistance prime and coating (water, sun, moisture, etc...)



NO-STOP tine with double spring



Fast hooking to the third point



Roller adjusting



Reinforced frame with structural 100x100 tube

Technical features

AGROMAK 5-F

100x100 mm Tubular Frame

Model	Tines	Discs	Power	Working width
AGROMAK 5F-5	5	6	75/100 cv	2.500 mm
AGROMAK 5F-7	7	8	105/140 cv	3.000 mm
AGROMAK 5F-9	9	10	135/180 cv	3.800 mm
AGROMAK 5F-11	11	12	165/200 cv	4.600 mm

Hydraulically foldable 100x100 mm Tubular Frame

Model	Tines	Discs	Power	Working width
AGROMAK 5F-H9	9	10	135/180 cv	3.800 mm
AGROMAK 5F-H11	11	12	165/220 cv	4.600 mm
AGROMAK 5F-H13	13	14	195/260 cv	5.400 mm
AGROMAK 5F-H15	15	16	225/300 cv	6.000 mm

AGROMAK-5F available options



Tine protected by a fusible link to be used in smooth soils



Tine protected with NO-STOP double spring for stony soils with stucks

