



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n
25215 SANT RAMON
(Lleida)
Tel.: +34 973 52 43 36
Fax: +34 973 52 43 81

www.seguessl.com
segues@seguessl.com
recanvis@seguessl.com
export@seguessl.com
administracio@seguessl.com



SEMI-CHISEL CHM

FRAME 80X80 & TINE 30X30



WWW.SEGUESSL.COM

SEGUÉS, since 1978 providing quality and performance

For an optimal tilling job over hard, stony, with stubble soils, etc... a strong implement, with tine clearance and with a high working depth versatility is required, the new **SEMI-CHISEL SEGUÉS CHM**

Advantages

- Two or three tine lines versions
- 30x30 tines
- 260 mm distance between tines in two lines versions
- 600 mm tine height
- 230 mm distance between tines in three lines versions
- Third point hitch
- New and innovative vertical folding system to reduce the transport width

CHM Strong points



CHM tine and frame clamp



Third point hitch



New vertical folding system



Roller height adjusting system



Springs pressure adjustment



Tine clamp to the frame



Two tine lines



Three tine lines

SEGUÉS CHM SEMI-CHISEL standard features

- Third point Hitch
- Ultra strong double spring system
- 40x40 tine
- Tines made in high quality cast iron
- Two sided shares made of Boron Steel
- Tines pressure adjustment
- Extra strength frame 80x80
- Prime and paint high resistant to corrosive agents (water, sun, moisture, fog... etc...)



Tines pressure adjustment



Two sided share made of boron steel



Reinforced frame with structural tubing



Third point hitch

Technical features

Semi-Chisel two 30x30 tine lines

Model	Foldable	Tines	Working width	Transport width	Power HP
CHM-7B	Fixed	7	1.820 mm	1.820 mm	65/75
CHM-9B	Fixed	9	2.340 mm	2.340 mm	75/85
CHM-11B	Fixed	11	2.860 mm	2.860 mm	90/100
CHM-13B	Fixed Hydraulic	13	3.380 mm	$\frac{3.380 \text{ mm}}{2.860 \text{ mm}}$	100/120
CHM-15B	Fixed Hydraulic	15	3.900 mm	$\frac{3.900 \text{ mm}}{2.860 \text{ mm}}$	120/135
CHM-17B	Hydraulic	17	4.420 mm	2.860 mm	135/145
CHM-19B	Hydraulic	19	4.940 mm	2.860 mm	150/165
CHM-21B	Hydraulic	21	5.460 mm	2.860 mm	165/170
CHM-23B	Hydraulic	23	5.980 mm	2.860 mm	170/185
CHM-25B	Hydraulic	25	6.500 mm	2.860 mm	190/210
CHM-27B	Hydraulic	27	7.020 mm	2.860 mm	+210

Semi-Chisel three 30x30 tine lines

Model	Foldable	Tines	Working width	Transport width	Power HP
CHM3F13B	Fixed	13	2.990 mm	2.990 mm	110/130
CHM3F16B	Fixed Hydraulic	16	3.680 mm	$\frac{3.680 \text{ mm}}{2.860 \text{ mm}}$	130/145
CHM3F18B	Hydraulic	18	4.140 mm	2.860 mm	140/155
CHM3F20B	Hydraulic	20	4.600 mm	2.860 mm	150/170
CHM3F22B	Hydraulic	22	5.060 mm	2.860 mm	170/180
CHM3F24B	Hydraulic	24	5.520 mm	2.860 mm	175/195
CHM3F26B	Hydraulic	26	5.980 mm	2.860 mm	185/205
CHM3F28B	Hydraulic	28	6.440 mm	2.860 mm	200/220
CHM3F30B	Hydraulic	30	6.900 mm	2.860 mm	215/235
CHM3F32B	Hydraulic	32	7.360 mm	2.860 mm	230/250
CHM3F34B	Hydraulic	34	7.820 mm	2.860 mm	+250

SEMI-CHISEL SEGUÉS available options



Roller with bearings protection



Comb made of 10mm springs