



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n
25215 SANT RAMON
(Lleida)
Tel.: +34 973 524 336
Fax: +34 973 524 381

www.seguessl.com
segues@seguessl.com
recanvis@seguessl.com
export@seguessl.com
administracio@seguessl.com

www.seguessl.com

SPS

MOUNTED FERTILIZER
DISTRIBUTORS 800 to 1.500 l



WWW.SEGUESSL.COM

Twin spinner and mounted fertilizer spreaders 800 to 1500 l

SPS MOUNTED DISTRIBUTORS



SEGUÉS, Specialists in fertilizer distribution

SEGUÉS SPS FERTILIZER DISTRIBUTORS STRONG POINTS:

- Distribution by twin spinner made in stainless steel
- Distribution system made 100% in stainless steel
- Hand adjustable regulation system, simple and intuitive
- Spinners mechanically driven by the PTO at 540 rpm
- Regulation and dosage tables for most common products
- Double drop inside the hopper, one per spinner
- Double mesh, one per drop to avoid blocks
- Double agitator to guarantee a regular flow
- Optional systems to locate the fertilizer in vineyards and orchards
- CAT I-II linking system

TECHNICAL FEATURES

Model	Upload	Hopper	Width	Length	Height	Weight
SPS800	1.200 kg	800 l	1.580 mm	1.110 mm	1.030 mm	185 kg
SPS1000	1.200 kg	1.000 l	1.580 mm	1.110 mm	1.180 mm	198 kg
SPS1200	1.200 kg	1.200 l	1.580 mm	1.110 mm	1.330 mm	210 kg
SPS1500	1.200 kg	1.500 l	2.020 mm	1.250 mm	1.370 mm	226 kg
SPS800X	1.200 kg	800 l	1.580 mm	1.110 mm	1.030 mm	185 kg
SPS1000X	1.200 kg	1.000 l	1.580 mm	1.110 mm	1.180 mm	198 kg
SPS1200X	1.200 kg	1.200 l	1.580 mm	1.110 mm	1.330 mm	210 kg
SPS1500X	1.200 kg	1.500 l	2.020 mm	1.250 mm	1.370 mm	226 kg

X models: stainless steel hopper

STANDARD FEATURES



Double (grill) mesh to avoid blocks, one per outlet



3 point linkage CAT I-II



Individual agitator, one per spinner for a regular flow



PTO driven spinners at 540 rpm



100% stainless steel distribution system



Tin spinner

AVAILABLE NON-STANDARD FEATURES FOR SPS SPREADERS



Wings kit to spread up to 24 m



Sides deflector



Hopper divisor



double side, adjustable and stainless steel conveyor



Adjustable tarpaulin



Round section outlet to be coupled in double side deflector



Open/close hydraulic controls



Storing support with wheels