



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n  
25215 SANT RAMON  
(Lleida) - Spain  
Tel.: +34 973 524 336  
Fax: +34 973 524 381

[www.segues.es](http://www.segues.es)  
[www.seguessl.com](http://www.seguessl.com)  
[www.segues.fr](http://www.segues.fr)  
[segues@seguessl.com](mailto:segues@seguessl.com)  
[export@seguessl.com](mailto:export@seguessl.com)



## SDI

HIGH-PRECISION TWIN DISC  
MOUNTED FERTILIZER  
SPREADER



[www.seguessl.com](http://www.seguessl.com)

[www.seguessl.com](http://www.seguessl.com)

## SEGUÉS, High precision in the distribution of fertilizers

SEGUÉS SDI fertilizer spreaders are highly accurate fertilizer distributors with high capacity and high reliability. With capacity to spread the SDI to 36 meters, they are undoubtedly essential machines to achieve optimum fertilization and the best possible harvest.

### KEY STRENGTHS:

- Hydraulic opening / closing
- Manual regulation of drop point of the fertilizer
- Fast lubrication system of the transmission
- Standard screen in all versions
- Transmission
- Fertilizer exit protector
- Inspection ladder
- Stainless steel hopper bottom
- Stainless distribution system
- Manual position adjustment of the pallets
- Very slow rotation agitator, 60 rpm
- High precision distribution up to 36 m
- Hoppers of 2,000 and 3,000 liters capacity.



### SERIAL EQUIPMENT:

- Manual regulation of the drop point of the fertilizer
- Screen and agitator at low revolutions
- Bottom of the stainless steel hopper
- Manual adjustment of the discharge flow of fertilizer
- Manual adjustment of the position of the pallets
- PTO transmission of the tractor at 540 rpm
- Inside view of the hopper
- Protector of the exit of the fertilizer



## Technical characteristics fertilizers Segués SDI



### SEGUÉS SDI 3000

With supplement of 1000 l mounted on top of the trailer for SDI, stainless distribution and manual regulation. Machine ready to start working in widths of up to 32 m. For higher widths you should change the pallets.

Model	Load	Hopper	Width	Length	Height	Weight
SDI1500	3.000 kg	1.500 l	2.500 mm	1.500 mm	1.180 mm	335 kg
SDI2000	3.000 kg	2.000 l	2.500 mm	1.500 mm	1.300 mm	360 kg
SDI3000	3.000 kg	3.000 l	2.500 mm	1.500 mm	1.560 mm	405 kg

### Optional equipment



Edges defflector



Discharge tube for calibration or emptying



SDI - Rear lights kit



Hopper cover



VRA System



GPS Teejet, Antenna for speed signal



Anti-wear paddle kit



Support with wheels