



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n
25215 SANT RAMON
(Lleida)
Tel.: +34 973 52 43 36

www.seguessl.com
www.segues.es
www.segues.fr
segues@seguessl.com
export@seguessl.com



CHH L/D

Hydraulic, Foldable and
Horizontal **LAND ROLLERS**



www.seguessl.com

www.seguessl.com

SEGUÉS, experts in soil work

The SEGUÉS CHH L/D Land rollers are characterized by it easy use, great performance on the field and the low maintenance cost. To this great usefulness, standouts also the width available measures range and the possibility to choose between a flat or a toothed surface.

Benefits

- Tubular frame made of extra strong structural steel.
- One piece cylinders made of High resistant steel ST-52
- 12 mm cylinder wall, same as 20 mm of regular steel.
- Filling cap in every cylinder
- The side sections overlap the middle section to cover the surface's 100%
- Very simple folding and unfolding manoeuvres.

Folding sequence of CHH 5 to 7 m



Folded (transport position)



Unfolding start (back up)



Unfolded land roller ready for working

Standard features

- Mechanical Jack
- Reinforced frame made of structural tubing
- Cylinders made of 12 mm high resistant steel ST-52 sheet, equivalent to 20 mm of regular steel sheet.
- Hydraulic folding movements
- Flat or toothed surface available
- Independent sections for the best all terrain adaptation
- Lights kit including:
 - Sidelights
 - Indicators
 - Brake light
- 10.0/75 - 15,3" as standard tyres in CHH-5 a 7
- 11.5/80 - 15,3" as standard tyres in CHHL-8 and under request for smaller land rollers



Lights kit, side lights, brake lights, indicators



Hydraulic movement and support jack



Results after rolling with toothed or flat land roller



Cylinder made with ST-52 steel sheet.

Technical Features

Model	Empty weight	Surface	Working width	Transport width	Length	Height	Wheel
CHHL-5	2.320 kg	Llis	5.000 mm	2.520 mm	3.670 mm	1.780 mm	10.0/75-15.3
CHHD-5	2.912 kg	Dentat	5.000 mm	2.520 mm	3.670 mm	1.780 mm	10.0/75-15.3
CHHL-6	2.440 kg	Llis	6.000 mm	2.520 mm	4.170 mm	1.780 mm	10.0/75-15.3
CHHD-6	3.147 kg	Dentat	6.000 mm	2.520 mm	4.170 mm	1.780 mm	10.0/75-15.3
CHHL-7	2.586 kg	Llis	7.000 mm	2.520 mm	4.670 mm	1.780 mm	10.0/75-15.3
CHHD-7	3.407 kg	Dentat	7.000 mm	2.520 mm	4.670 mm	1.780 mm	10.0/75-15.3
CHHL-8	4.040 kg	Llis	8.000 mm	2.570 mm	5.250 mm	2.010 mm	11.5/80-15.3



Unfolding sequence CHHL-8



CHHL-8 ready for transport



CHHL-8's folding and unfolding sequence



CHHL-8 ready for rolling