



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n
25215 SANT RAMON
(Lleida) -Spain
Tel.: +34 973 524 336

www.segues.es
www.seguessl.com
www.segues.fr
segues@seguessl.com
export@seguessl.com

www.seguessl.com

DISCSEG



Fast Disc Harrow 2.5 - 8 m



www.seguessl.com

FAST DISC HARROW -DISCSEG

MAQUINARIA AGRICOLA SEGUÉS at the farmer's side since 1978
SEGUÉS DISCSEG fast disc harrows are the best tool for working with the soil at shallow depth and at high speed, achieving in a single pass, that all the crop and stubble remains are crushed and perfectly mixed with the earth, and without unevening the soil.

The strengths of the DISCSEG fast disc harrow are:

- Suspended fast disc harrows from 2.5 to 6 suspended and dragged from 8 m.
- From 4 m of hydraulic folding and allows the option of being dragged.
- Trailed stands have a drawbar and 2 400/60 15.5 wheels as standard.
- Independent discs of 560 or 610 mm
- Rubber cushioning, independent hub on each disc
- Distance between rows of 1,000 mm
- 250 mm distance between discs
- Sealed hubs with double tapered bearings. There is the option of free maintenance.
- CAT II and III hitch
- Optimum inclination of the discs adjusted at the factory
- Low maintenance and easy to use.
- Roller to choose between several types

Lightweight 2.5 and 8 meter fast disc harrows

OPTIONAL EQUIPMENT FOR THE TRAILED HARROW

- Wheels 500 / 50-12
- Hydraulic brake
- Pneumatic brake



ADVANTAGES:



560 or 610mm independent discs



Optional maintenance-free standard double bearing bushings



Optimum position of the discs

TECHNICAL CHARACTERISTICS

WORKING WIDTH (mm)	2.5		2.7		3.0		4.0	
WIGHT (Kg)	1.150		1.250		1.380		1.900	
Nº OF DISCS / BUSHINGS	20		22		24		32	
REQUIRED POWER (cv)	60/90		75/110		80/110		100/130	
DISC DIAMETER(mm)	560	610	560	610	560	610	560	610

WORKING WIDTH (mm)	4.0H*		4.5H*		5.0H*		6.0H*		8.0HA*	
WEIGHT (Kg)	3.060		3.500		3.850		4.650		6.250	
Nº OF DISC / BUSHINGS	32		36		40		48		68	
REQUIRED POWER (cv)	130/160		150/180		160/200		180/260		<250	
DISC DIAMETER(mm)	560	610	560	610	560	610	560	610	560	610

H* - Hydraulic folding
HA* - Trailed with hydraulic folding

ROLLERS AVAILABLE



500 or 600 mm diameter Packer roller



Rings roller



500mm diameter bar roller



500 mm diameter rubber roller