



**MAQUINARIA AGRÍCOLA SEGUÉS S.L.**

Av. Santuari s/n  
25215 SANT RAMON  
(Lleida) - Spain  
Tel.: +34 973 524 336

[www.segues.es](http://www.segues.es)  
[www.seguessl.com](http://www.seguessl.com)  
[www.segues.fr](http://www.segues.fr)  
[segues@seguessl.com](mailto:segues@seguessl.com)  
[export@seguessl.com](mailto:export@seguessl.com)



# PL y SRT

**SINGLE DISC SUSPENDED  
SALT SPREADERS**



[www.segues.es](http://www.segues.es)

[www.segues.es](http://www.segues.es)

**SEGUÉS AGRICULTURAL MACHINERY at the farmer's side since 1978**

The PL salt and sand distributors are equipped with a polyethylene or stainless steel hopper resistant to the chemical aggressions of salt and antifreeze products, they are perfect for road maintenance work. If you want to limit the working width, they can be equipped with a deflector that will allow us to work in any space with total comfort.

**STRENGTHS POINTS:**

- Distribution by centrifugal disc.
- 100% adjustable distribution system.
- Simple and intuitive dosage regulation system.
- Regulation of the area of the disc where the salt must fall.
- Standard screen to avoid jams and the entry of foreign bodies.
- Small agitator at the product outlet for correct feeding of the disc.
- Special systems for salt.

**PL SPREADER****PL SERIES EQUIPMENT**

- Agitator and sieve to avoid jams and entry of foreign bodies.
- Disc and 4 stainless steel vanes.
- Polyethylene hopper
- Mechanical drive of the disc through PTO at 540rpm.
- Opening and closing by means of a lever.
- Coupling to the 3 point CAT I-II.
- Working width of 1-6m

**TECHNICAL CHARACTERISTICS PL SPREADER**

Model	Capacity		Width	Length	Hight	Weight	Power
PL-500	400 kg	350 l	1.230 mm	1.240 mm	1.140 mm	60 kg	30 cv

**SRT SPREADER****SRT SERIES EQUIPMENT:**

- Stainless steel screen to avoid jams and entry of foreign bodies.
- Stainless steel disc and vanes.
- Stainless steel hopper.
- Hydraulic drive.
- Powered by tractor PTO.

**TECHNICAL CHARACTERISTICS SRT SPREADER**

Model	Capacity		Width	Length	Hight	Weight	Power
SRT-800-PRO	740 kg	800 l	1.500 mm	1.295 mm	1.020 mm	155 kg	30 cv
SRT-1000-PRO	930 kg	1.000 l	1.500 mm	1.295 mm	1.045 mm	168 kg	30 cv